

Single-width, C-size Module that combines the high performance of a Pentium 4-based computer with the functionality of a VXI Slot-0 controller. A cost-effective and high-performance Slot-0 controller solution for your data collection needs.

TYPICAL APPLICATIONS

Aerospace and aircraft testing
High-performance ATE
High-performance data acquisition and control

V153

Embedded Pentium 4 Slot-0 Controller



Single-width, C-size module that combines the performance of a Pentium 4-based computer with the functionality of a VXI Slot-0 controller

FEATURES

- Single-width C-size module
- High-performance Pentium 4 embedded processor with clock options 1.7GHz and 2.2GHz
- Windows XP Operating System supported
- Ideal for high-performance data acquisition and control
- One Ethernet controller supporting 10BaseT and 100BaseTX interfaces
- Secondary Ethernet controller supporting 10BaseT, 100BaseTX and 1000BaseT interfaces
- Front panel Universal Serial Bus (USB) connection Rev. 2.0
- Up to 1 Gbyte bootable flash on secondary IDE
- Up to 1 Gbyte PC1600 DDR SDRAM
- PMC expansion site



GENERAL DESCRIPTION

The V153 is a single-width, C-size module that combines the performance of a Pentium 4-based computer with the functionality of a VXI Slot-0 controller. Alternatively, on-board strap options enable this module to be used as a VXI-based processor in non-Slot-0 applications.

The V153's optional External CD-ROM drive allows for the installation of a number of popular programming environments and compilers, including Microsoft Visual C++.

For soft real-time applications, the V153 coupled with the Windows XP operating system is a cost-effective and high-performance Slot-0 controller solution for your data collection needs.

As technology increases the capacity of hard drives changes. Be sure to contact KineticSystems for the latest hard drive offerings.

Item	Specification
Processor Options	Pentium 4 Processor 1.7 GHz Pentium 4 Processor 2.2 GHz
DDR SDRAM	Options available with 256 Mbyte, 512 Mbyte and 1 Gbyte
Internal Hard Drive	40 GB IDE Hard Drive, contact KineticSystems for latest hard drive offerings
Timers and Watchdog Timer	Two 16-bit timers and two 32-bit timers and software programmable watchdog timer
Compact Flash Memory	Supports up to 1 GB of Compact Flash through secondary IDE port
RTC/NVSRAM	Real Time Clock and 32 KB of nonvolatile SRAM
Ethernet Interface	Dual Ethernet controllers supporting 10BaseT, 100BaseTX and 1000BaseT interfaces
PMC Slots	5 V signaling, types 1 and 2, 32-bit PCI bus, 33 MHz maximum
Graphics Support	Internal Graphics Controller (852 GME chip set) w/ Digital Visual Interface (DVI). Up to 1600 x 1200 Resolution
USB Port	Supports one USB Rev. 2.0
Environmental and Mechanical	
Temperature Range	
Operational	0 to +50 degrees C
Storage	-25 to 75 degrees C
Relative Humidity	0 to 86% non-condensing to 40 degrees C
Dimensions	340mm x 233.35mm x 30.48mm (C-size VXIbus)
Vibration and Shock	
Operating Vibration	9.8m/s ² (1.0G), 5-500 Hz
Operating Shock	1470m/s ² (150G)
Non-Operating Shock	6860m/s ² (700G)
Power Requirements	
+5V	10200 mA
-5.2V	270 mA
-2V	96 mA
+12V	100 mA
-12V	100 mA

900 N. State St.
Lockport, IL 60441-2200

Toll-Free (US and Canada):
phone 1-800-DATA NOW
1-800-328-2669

Direct:
phone +1-815-838-0005
fax +1-815-838-4424

Email:
mkt-info@kscorp.com

To find your local sales representative or distributor or to learn more about KineticSystems' products visit:

www.kscorp.com

ORDERING INFORMATION	
Description	Part Number
VMIC 7805 P4, 1.7 GHz, 256 MB, 40 GB Hard Drive	V153-AC11
VMIC 7805 P4, 1.7 GHz, 512 MB, 40 GB Hard Drive	V153-AC12
VMIC 7805 P4, 1.7 GHz, 1 GB, 40 GB Hard Drive	V153-AC13
VMIC 7805 P4, 2.2 GHz, 256 MB, 40 GB Hard Drive	V153-AD11
VMIC 7805 P4, 2.2 GHz, 512 MB, 40 GB Hard Drive	V153-AD12
VMIC 7805 P4, 2.2 GHz, 1 GB, 40 GB Hard Drive	V153-AD13

Updated February 20, 2007

Copyright © 2006, 2007 DynamicSignals, LLC. All rights reserved.